

ENSTO

SLIP22.1

Zacisk przebijający izolację

- Typ SLIP22.1
- GTIN 6418677403842
- Nazwa Zacisk przebijający izolację
(Al 10-95 mm² lub Cu 1.5-70 mm²) i (Al 10-95 mm² lub Cu 1.5-70 mm²)
- Opis Zacisk SLIP 22.1 stosowany jest do łączenia izolowanych przewodów nn aluminiowych lub miedzianych w dowolnej konfiguracji. Konstrukcja zacisku umożliwia montaż zacisku pod napięciem. Zacisk wyposażony jest w śrubę z łbem zrywalnym. Łeb zrywalny jest odizolowany od śruby i korpusu zacisku.

EAC



Specyfikacje techniczne

Wymiary

Masa:	0.12 kg
Żył główna mm ² :	Al 10-95 / Cu 1.5-70
Przewód rozgałęźny mm ² :	Al 10-95 / Cu 1.5-70
Średnica żyły:	3 ... 16 mm

Parametry elektryczne

Najwyższe napięcie systemu:	1 kV
-----------------------------	------

Features

Bolt:	M8x50
-------	-------

Mechanical

Moment dokręcenia:	17-20 Nm
--------------------	----------

Ratings

ETIM 7:	EC001062 Branch terminal
---------	--------------------------

Specyfikacja

Use:	All connections of insulated aluminium and copper main and branch conductors up to 1000 VAC. The design enables hot line installation.										
Construction:	The teeth inside the connector are greased to retard water entry and corrosion of aluminium conductors.										
Construction:	<table> <tr> <th>Component</th><th>Material</th></tr> <tr> <td>Body</td><td>Tin coated corrosion resistant aluminium alloy</td></tr> <tr> <td>Spring plate</td><td>Stainless spring steel</td></tr> <tr> <td>Screw</td><td>Hot dip galvanized, shearhead 13 mm</td></tr> <tr> <td>Cover</td><td>Weather and UV-radiation resistant plastic</td></tr> </table>	Component	Material	Body	Tin coated corrosion resistant aluminium alloy	Spring plate	Stainless spring steel	Screw	Hot dip galvanized, shearhead 13 mm	Cover	Weather and UV-radiation resistant plastic
Component	Material										
Body	Tin coated corrosion resistant aluminium alloy										
Spring plate	Stainless spring steel										
Screw	Hot dip galvanized, shearhead 13 mm										
Cover	Weather and UV-radiation resistant plastic										
Installation:	Remove conductor inlet caps according to the connection to be made. Open the upper lid. Unscrew the screw until the conductors can be placed into the connector. Tighten the screw until the shearhead breaks. Shut the upper lid.										
Tools required:	Wrench CT164 and fork wrench ST34.										
Markings:	ENSTO, SLIP 22.1, Al 10-95 mm ² , Cu 1.5-70 mm ²										
Standard:	EN 50483-4										

ETIM

ETIM

Nominal cross section main conductor, SM: 10 ... 95 mm²

Nominal cross section main conductor, SE: 10 ... 95 mm²

Material main conductor: Aluminium/copper

Nominal cross section branch conductor, SE/RE: 1.5 ... 70 mm²

Clamping channel opening main conductor: Closed

Surface protection: Tinned

Terminal insulated: true

Material branch conductor: Aluminium/copper

Type of connection: Insulation piercing connector IPC

Clamping channel opening branch conductor: Closed

Nominal cross section branch conductor, SM/RM: 1.5 ... 70 mm²

Opakowanie

Opakowanie

Unit: PCS

Size: 50

Length:	385 mm
Width:	260 mm
Height:	165 mm
Weight (brt):	6.2 kg
Volume:	0.0165

Pallet package

Unit:	PCS
Size:	2700
Length:	1200 mm
Width:	800 mm
Height:	1140 mm
Weight (brt):	355 kg
Volume:	1.0944

