

ENSTO

KE61

Zacisk Clampo Pro

Typ	KE61
GTIN	6418677191817
Nazwa	Zacisk Clampo Pro Ensto Clampo Pro 1 torowy, szary, Al 6-50 mm ² , Cu 2.5-50 mm ²
Opis	Zaciski uniwersalne Ensto Clampo stosowane są do łączenia przewodów Al/Cu o przekrojach 2.5 – 240 mm ² . Szeroki zakres zastosowań od tradycyjnych rozdzielnic, automatykę kontrolno-pomiarową, po instalacje budownictwa mieszkaniowego.
Producent	Ensto Finland Oy



Specyfikacje techniczne

Wymiary

Masa:	0.03 kg
Przekrój żyły:	Cu 2,5-50 Al 6-50

Temperatura

Temperatura pracy:	≤ 80 °C
--------------------	---------

Parametry elektryczne

Nominal insulation voltage:	800 V
Nominal current:	Cu 160 A, Al 145 A
Stopień zanieczyszczenia:	3

Materiał

Obudowa:	Poliamid
----------	----------

Kolor

Kolor:	Szary
--------	-------

Features

Liczba biegunów:	1
Łeb śruby:	Sześciokąt

Screw head size:	5 mm
Montaż:	Listwa DIN
Mechanical	
Moment dokręcenia:	4 Nm (2.5-4mm ²), 12 Nm (6-50mm ²)

Certyfikaty

Standardy:	EN 60947-7-1, EN 61238-1
Klasa zwarciowa:	A
Kategoria UL:	XCFR2
Nr specyfikacji UL:	E192532, E192532

Ratings

ETIM 7:	EC000897 Feed-through terminal block
----------------	--------------------------------------

US specific

Rozmiar żyły:	1/0-6
Napięcie maksymalne:	600 V
Moment dokręcenia:	90 Lb-In
Prąd maks.:	Cu 150A, Al 120A

ETIM

ETIM

Length:	49 mm
Material insulation body:	Thermoplastic
Rated voltage:	800 V
Width/grid dimension:	17.8 mm
Mounting method:	DIN rail (top hat rail) 35 mm
Colour:	Grey
Type of electrical connection 1:	Screw connection
Number of levels:	1
Height at lowest possible mounting height:	43 mm
Operation temperature:	-5 ... 80 °C
Connectable conductor cross section fine-strand with cable end sleeve:	2.5 ... 35 mm ²
Number of clamp positions per level:	2
Connectable conductor cross section fine-strand without cable end sleeve:	2.5 ... 35 mm ²
Explosion-tested version 'Ex e':	false
Connectable conductor cross section multi-wired:	2.5 ... 50 mm ²
Inflammability class of insulation material acc. with UL94:	V2
Rated current In:	145 A
Type of electrical connection 2:	Screw connection
Connection position:	Sideways

Opakowanie

Opakowanie

Unit:	PCS
Size:	30
Length:	220 mm
Width:	220 mm
Height:	125 mm
Weight (net):	0.923 kg
Weight (brt):	1.059 kg
Volume:	6.05